

713SX2

700SX2 - 2000/2500 W TUNGSTEN



- **Type:** Profile spot
- **Source:** 2000/2500 W Tungsten
- **Optics:** 29° to 50° zoom

Profile spot

The ideal zoom profile for all short throw applications

Combining power with a smooth flat beam, the 713 SX2 is the perfect profile for all short throw applications in medium to large theatres and opera houses. Its secure G22 lamp socket ensures reliability, longer lamp life, and 2000 W or 2500 W lamp options.

Features

- **Multi-function double gate:** simultaneous use of gobos and iris. Sharp focus of both gobo and shutter
- **Shutter gate:** up to 8 shutters. Remove shutters for easy maintenance or tuck fully inside gate for secure transport
- **User-friendly shutter-lock system:** secures shutters' setting in any circumstances (locking efficient up to 4 shutters)
- **Universal gobo holder:** "A" size glass and metal gobo
- **Lens tube lock feature:** secures rotating lens tube against unwanted movement
- **90° rotating lens tube / gate / front accessories holder:** rotation of the projected image is always possible while the lamp remains vertical – no need to move the yoke
- **Internal glass filter holder:** long term use of durable coloured, dichroic or textured glass
- **Easy focus reference:** graduated scale on side of the unit; fast and easy refocusing
- **Tilt reference on hanging yoke:** index for rapid re-positioning

Optical

- **Factory set optical train:** no re-alignment even after lamp change
- **SX optical system:** double condenser optics for exceptional optical quality
- **Variable zoom optics:** sharp focus at every beam angle. Independent control of image size and focus. Focus handles on both sides

Construction

- **Made in France :** fully manufactured in Robert Juliat premises retaining complete control over all aspects of quality
- **G22 socket locking system exclusive to Robert Juliat:** holds the lamp securely in place to ensure there is no arcing, even when the fixture is pointing vertically downward
- **Silent-running cooling fans:** ideal for TV studios and opera houses
- **Bodywork:** strong sheet metal construction for durability
- **Moving parts:** smooth at all times, even when hot
- **Captive knobs and handles:** additional security when working at height or in transit
- **Easy access to all parts:** easy cleaning, re-lamping and maintenance
- **Removable assemblies:** fast-plug cable connectors and complete component assemblies (mirror, condenser set and lamp house assembly) save maintenance and cleaning time
- **Spare parts and accessories:** interchangeable across the tungsten, discharge or LED ranges, reducing running costs

Picture:713SX2

DSEN071_713SX2 - 06/04/2021


Robert Juliat reserves the right to change or alter any of the items detailed on this page, to increase or improve manufacturing techniques without prior notice.

Robert Juliat S.A.S., 32 rue de Beaumont, 60530 Fresnoy-en-Thelle - France
Telephone : +33 (0)3 44 26 51 89 - fax : +33 (0)3 44 26 90 79 - info@robertjuliat.fr
www.robertjuliat.com



ROBERT JULIAT

Source



- **Lamp type:** Tungsten
- **Socket:** G22

| Admissible lamps | Power * | Lumen output* | Colour temperature* | Life* |
|------------------|---------|---------------|---------------------|-------|
| LIF: CP92 | 2 000 W | 52 000 lm | 3200K | 400 h |
| LIF: CP91 | 2 500 W | 65 000 lm | 3200K | 400 h |

(*) manufacturer's data

Optics

Characteristics


- **Type:** Zoom
- **Beam range:** 29° to 50°
- **Focal length:** 86 - 155 mm

Gel filter

- **Shape:** Square
- **Standard size:** 215x215 mm (8.5x8.5 in)

Gobo



- **Size:** A
- **Material:** Metal
Glass



Photometrics

with LIF: CP91 source



• Optics @ 29°



Beam intensity
160 000 cd

| | | | | | | |
|---------------------|-----------|-----------|---------|---------|---------|---------|
| Distance | 5 m | 10 m | 15 m | 20 m | 25 m | 30 m |
| Diameter | 2.6 m | 5.2 m | 7.8 m | 10.3 m | 12.9 m | 15.5 m |
| Illumination | 6 500 lux | 1 650 lux | 720 lux | 410 lux | 260 lux | 180 lux |
| Distance | 15 ft | 35 ft | 50 ft | 65 ft | 80 ft | 100 ft |
| Diameter | 7.8 ft | 18.1 ft | 25.9 ft | 33.6 ft | 41.4 ft | 51.7 ft |
| Illumination | 720 fc | 140 fc | 65 fc | 38 fc | 26 fc | 17 fc |


• Optics @ 50°



Beam intensity
56 000 cd

| | | | | | | |
|---------------------|-----------|---------|---------|---------|---------|---------|
| Distance | 5 m | 10 m | 15 m | 20 m | 25 m | 30 m |
| Diameter | 4.7 m | 9.3 m | 14 m | 18.7 m | 23.3 m | 28 m |
| Illumination | 2 250 lux | 570 lux | 250 lux | 150 lux | 90 lux | 65 lux |
| Distance | 15 ft | 35 ft | 50 ft | 65 ft | 80 ft | 100 ft |
| Diameter | 14 ft | 32.6 ft | 46.6 ft | 60.6 ft | 74.6 ft | 93.3 ft |
| Illumination | 250 fc | 46 fc | 23 fc | 14 fc | 9 fc | 6 fc |

Dimensions and weight



Weight: 18 kg (39.6 lbs)

| Height | Length | Width | Yoke | Tilt | Option |
|---------------------|----------------------|---------------------|---------------------|----------|-----------------|
| H= 525 mm (20.7 in) | L= 655 mm (25.8 in) | W= 380 mm (15 in) | Y= 325 mm (12.8 in) | TU= TBD° | O= 25 mm (1 in) |
| H1= 250 mm (9.8 in) | L1= 265 mm (10.4 in) | W1= 250 mm (9.8 in) | | TD= TBD° | |
| H2= 330 mm (13 in) | L2= 390 mm (15.4 in) | | | | |

Shipping

- **Weight :** 22 kg (48.4 lbs)
- **Volume :** .13 m³ (4.59 ft³)

Installation

- **Minimum distance to illuminated surface:** 1.5 m (4.9 ft)
- **Operating position:**



Warranty

- **Fixture: 2 years**
See General Sales Condition on website

Approvals



Construction

- **Housing:** Steel sheet - Aluminium
- **Colour:** Black
- **Cooling:** Low noise fan
- **Maximum ambient temperature (Ta):** 40°C (104°F)
- **Maximum case temperature (Tc):** 270°C (518°F)
- **Total heat dissipation:** 6 826 BTU/h
- **Ingress Protection (IP) rating:** IP20

Electrical compatibility

- 230/240 V - 50 Hz
- ~~115/120 V - 60 Hz~~

Power input



- **Type:** attached power cord
- **Cable:** H07RNF 3G1.5
- **Length:** 3 m (9.8 ft)
- **Power connector:** CEE 7/7 (2P+E NF/Schuko)




Power consumption

| Voltage | Frequency | Current | Power |
|---------|-----------|---------|--------|
| 230 V | 50 Hz | 9 A | 2000 W |
| 230 V | 50 Hz | 11 A | 2500 W |














Model




| | |
|---------------|--|
| 713SX2 | 2000/2500 W Tungsten Profile spot - G22 socket - 713SX2 - 29/50° |
|---------------|--|

Options

| | | |
|-----------------|--|---|
| CAV700 | Double slot front cassette for 215x215mm accessories |  |
| CAV700J | Double slot front cassette for 245x245mm accessories |  |
| PCP1716A | 16A blue 2P+E 6h IEC60309 power connector |  |

Accessories

| | | |
|-----------------|---|---|
| D8 | Shutter for SX series 4 included |  |
| PF1000M2 | 215x215mm metal filter holder 1 included |  |
| SGUX | Universal "A" size gobo-holder (metal, glass, frosted glass) 1 included |  |
| CP91 | CP91 - G22 2500W 230V 400h 3200K lamp |  |
| CP92 | CP92 - G22 2000W 230V 400h 3200K lamp |  |
| IWSX755 | Drop-in iris (monoplane) with holder - Poids: 0.26 Kg |  |
| G1000 | 215x215mm safety grid |  |
| CAV700A | Double slot front cassette for 215x215mm accessories - Poids: 0.52 Kg |  |
| CAV700AJ | Double slot front cassette for 245x245mm accessories - Poids: 0.95 Kg |  |
| RPF713 | Front extension cassette for 215x215mm accessories without fan - Poids: 1.5 Kg |  |
| RV934 | Front extension cassette for 215x215mm accessories with fan - Poids: 2 Kg |  |
| VD120 | 120x120mm frosted glass |  |
| FCD700 | Angled yoke - Poids: 1.62 Kg |  |

| | | |
|------------|---|---|
| 876 | Hook clamp 40x10mm with 28mm M10 screw for Ø35 to 50mm pipes - SWL: 50Kg - Poids: 1.25 Kg |  |
| 880 | Hook clamp 40x10mm with 28mm M10 screw for Ø50 to 63mm pipes - SWL: 50Kg - Poids: 1.36 Kg |  |
| CS2 | Safety cable Ø3 mm L= 600mm - SWL: 75 Kg |  |